

POLYURETHANE

FEATURES



DRAUGHTSMAN

BACKREST	Black injection moulded polyurethane foam, average THK 25 mm, on a black polypropylene support, THK 5 mm.
SEAT	Black injection moulded polyurethane foam, average THK 25 mm, on a pressed wood support, THK 10 mm.
CONNECTOR ROD	Steel connector rod finished with black epoxy paint, section 45 x 6 mm, firmness 42 kg/mm ² . Accordeon type protective rod sheath made from expanded polyethylene, THK 1.5 mm. Seat support plate made from pressed steel, average THK 2.5 mm, black epoxy paint finish.
BASE	5-point star base Polyamide with metal ring, ø 640 mm. Gas lift mechanism, black epoxy finish, adjustment range of 244 mm Glides As standard: 5 black nylon glides Attachment: clip-on to steel axel ø 11 mm.



TASK CHAIR

BACKREST	Black injection moulded polyurethane foam, average THK 25 mm, on a black polypropylene support, THK 5 mm.
SEAT	Black injection moulded polyurethane foam, average THK 25 mm, on a pressed wood support, THK 10 mm.
CONNECTOR ROD	Steel connector rod finished with Black epoxy paint, section 45 x 6 mm, firmness 42 kg/mm ² . Accordeon type protective rod sheath made from polyethylene. Seat support plate made from pressed steel, average THK 2.5 mm, black epoxy paint finish.
BASE	5-point star base Black nylon, ø 600 mm. Gas lift mechanism, black epoxy finish, adjustment range of 127 mm Castors As standard: 5 castors with twin rollers made from black nylon, ø 50 mm, clip-on attachment to steel axel ø 11 mm. Attachment: clip-on to steel axel ø 11 mm.





STOOL

SEAT	Black injection moulded polyurethane foam, average THK 55 mm, on a pressed wood support, THK 10 mm.
CONNECTOR ROD	Seat support plate made from pressed steel, average THK 20/10th
BASE	<p>5-point star base Black nylon, ø 600 mm. Gas lift mechanism, black epoxy finish, adjustment range of 190 mm</p> <p>Glides As standard: 5 black nylon glides ø 50 mm Attachment: clip-on to steel axel ø 11 mm.</p>

DIMENSIONS & WEIGHT

	DRAUGHTSMAN CHAIR	OFFICE CHAIR	STOOL
			

OVERALL DIMENSIONS (in mm)			
Width	ø 640	ø 600	ø 600
Depth	ø 640	ø 600	ø 600
Height	925	740	540
USEFUL DIMENSIONS (in mm)			
Seat height	534 / 778	398 / 525	480 / 670
Width x Seat depth	460 x 441	460 x 441	350 x 335
Backrest height (Distance between top of backrest/top of seat)	380	380	145